

Type SRX

<u>FUNCTION</u>	<u>ENCLOSURE</u>	<u>CONDUIT</u>	<u>OUTPUT DRIVE</u>	<u>INDICATOR</u>	<u>I.S. MARKING-ATEX</u>	<u>FEATURE DESIGNATOR</u>
17 - (2) SPDT Gold Contact Mechanical Switch (Passive Device) up to 0.5 amps @ 30VDC	S - 316SS Cover & Housing	5 - (2) M20 x 1.5	L - NAMUR Output 15mm	R - RED CLOSED / GREEN OPEN (ABS material of construction)	- Z - Volt Free Contact Switch	xx - Feature (see Note 1)
40 - (2) SPST or SPDT Reed Switch (Passive) 0.15 Amps @ 30VDC	9 - Aluminium Cover & Housing	B - (2) 1/2" NPT	M - NAMUR Output 25mm	C - 0 - 100% GRADUATED (ABS material of construction)	- Y - Certified Proximity Sensor Type 1	
42 - (2) V3 Style Proximity Sensor ATEX Certified to Exia IIC T4/T5/T6			S - 2 Pin Drive	O - NO VISUAL INDICATOR	- W - Certified Proximity Sensor Type 2	
43 - (2) Non V3 Style Proximity Sensor ATEX Certified to Exia IIC T4/T5/T6					- V - Certified Transmitter (with optional Type 2 sensors)	CERTIFICATION -RC - Custom Union Certified Added after Feature to denote unit is CU certified version
52 - (3 to 6) V3 Style Proximity Sensor ATEX Certified to Exia IIC T4/T5/T6					- U - Certified Proximity Sensor Low Temperature -Type 2	
53 - (3 to 6) Non V3 Style Proximity Sensor ATEX Certified to Exia IIC T4/T5/T6					- T - Certified Proximity Sensor Low Temperature -Type 1	
56 - (3 to 6) SPDT Gold Contact Mechanical Switch up to 0.5 amps @ 30VDC					- J - Certified Transmitter (with optional Volt free switches)	
59 - (3 to 6) SPST or SPDT Reed Switch (Passive Device) 0.15 Amps @ 30VDC					- H - Certified Transmitter - Non Contact (with optional Type 2 sensors)	

70 - POSITION TRANSMITTER
4-20mA @ 10 - 30 VDC - Certified Exia IIC T4/T5/T6
monitor may include up to 2 additional switch/sensors from functions 17, 40, 42 or 43

Part Number Compilation:

SRX17S5SRZ00-RC

NOTE 1:
The exact detail of switches/sensors/transmitters fitted in the monitor is not fully specified by the basic part number. The last 2 digits of the 'feature designator' provides a mechanism for cross-referencing to a centralised log establish the make and model of parts fitted in a given unit.

FURTHER NOTES:
Function assemblies 17, 40, 42 and 43 use a short cover. Where function 43 uses cylindrical sensors longer than 36mm, a tall cover is used. Function 52, 53, 56, 59 and 70 use a tall cover.

REV	DRAWN	DATE	CHK'D	ECO	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: 3.2 microns TOLERANCES: LINEAR: ±0.25mm ANGULAR: ±0.5°	TITLE:
	PT	11.8.14		14-2268		SRX Master Model Description - Exi Custom Union

This private & confidential drawing is the property of Imtex Controls Limited, Tonbridge, UK and cannot be copied or reproduced without the express written permission of the Company.	Imtex Controls Limited Deeside, Flintshire United Kingdom. Tel:+44(0)870-0340002 Website: www.imtex-controls.com	DEBUR AND BREAK SHARP EDGES	DWG NO. A190308	REV
		MATERIAL:		STATUS
		WEIGHT(g):	SCALE:1:1	SHEET 1 OF 1